



enventives

# VEN-LUBE™ V

## RECOMMENDATIONS

Ven-Lube™ V is recommended for use in total system treatment at a 1-3 lb/bbl concentration. Ven-Lube™ V is easily dispersed and should be added through the hopper directly into the active system or directly into the mud pits.

Ven-Lube™ V has been developed to provide superior friction reduction and aid in solids suspension.

## GENERAL INFORMATION

Ven-Lube™ V is a proprietary blend consisting of modified fatty acid derivatives and surfactants developed specifically as a high performance calcium tolerant drilling fluid lubricant. Engineered for use in both aqueous and non-aqueous based fluids Ven-Lube™ V provides a lubricious coating to metal surfaces and particles in the fluid and well bore. Ven-Lube™ V is oil soluble and easily dispersible in water.

## PACKAGING

Ven-Lube™ V is packaged in fifty five (55) gallon drums or five (5) gallon buckets. Prices for special packaging will be quoted on request.

## TYPICAL PROPERTIES

Form	: Viscous Liquid
Color	: Yellow-Brown
Odor	: Mild
pH	: 3.0-5.0
Specific Gravity	: 0.80-0.95
Stability	: 14 hrs at 300°

## PRECAUTIONS

See the Safety Data Sheet for more detailed information concerning storage, handling, transportation, disposal and safety requirements.